

Яндекс

Рефлексия в C++14

Antony Polukhin
Полухин Антон

Boost libraries author (DLL, TypeIndex)
Boost libraries maintainer (Any, Conversion, LexicalCast, Variant)

Структура

```
struct complicated_struct {  
    int i;  
    short s;  
    double d;  
    unsigned u;  
};
```

XMMM...

```
#include <iostream>
```

```
#include "magic_get.hpp"
```

```
struct complicated_struct { /* ... */};
```

```
int main() {
```

```
    using namespace pod_ops;
```

```
    complicated_struct s {1, 2, 3.0, 4};
```

```
    std::cout << "s == " << s << std::endl;    // Compile time error?
```

```
}
```

Но как?..

```
antoshkka@home:~$ ./test
```

```
S == {1, 2, 3.0, 4}
```

А ЧТО В ЗАГОЛОВОЧНОМ файле?

```
#include <iostream>
```

```
#include "magic_get.hpp"
```

```
struct complicated_struct { /* ... */};
```

```
int main() {
```

```
    using namespace pod_ops;
```

```
    complicated_struct s {1, 2, 3.0, 4};
```

```
    std::cout << "s == " << s << std::endl;    // Compile time error?
```

```
}
```

Пошло интереснее...

```
template <class Char, class Traits, class T>
std::basic_ostream<Char, Traits>&
    operator<<(std::basic_ostream<Char, Traits>& out, const T& value)
{
    flat_write(out, value);
    return out;
}
```

Так-так...

```
template <class Char, class Traits, class T>
void flat_write(std::basic_ostream<Char, Traits>& out, const T& val) {
    out << '{';
    detail::flat_print_impl<0, flat_tuple_size<T>::value >::print(out, val);
    out << '}';
}
```


WTF?..

```
template <std::size_t FieldIndex, std::size_t FieldsCount>
struct flat_print_impl {

    template <class Stream, class T>
    static void print (Stream& out, const T& value) {
        if (!!FieldIndex) out << ", ";
        out << flat_get<FieldIndex>(value);           // std::get<FieldIndex>(value)
        flat_print_impl<FieldIndex + 1, FieldsCount>::print(out, value);
    }

};
```

Wow!..

```
/// Returns const reference to a field with index `I`
```

```
/// Example usage: flat_get<0>(my_structure());
```

```
template <std::size_t I, class T>
```

```
decltype(auto) flat_get(const T& val) noexcept;
```

```
/// `flat_tuple_size` has a member `value` that constains fields count
```

```
/// Example usage: std::array<int, flat_tuple_size<my_structure>::value > a;
```

```
template <class T>
```

```
using flat_tuple_size;
```

Как подсчитать количество
полей в структуре?



Идея! (количество полей)

```
static_assert(std::is_pod<T>::value, "")
```

Идея!

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

Идея!

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

```
sizeof...(args) <= fields count
```

```
typeid(args)... == typeid(fields)...
```

Идея!

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

```
sizeof...(args) <= fields count
```

```
typeid(args)... == typeid(fields)...
```

Идея!

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

```
sizeof...(args) <= fields count
```

```
typeid(args)... == typeid(fields)...
```

```
sizeof(char) == 1
```

```
sizeof...(args) <= sizeof(T)
```


Идея!

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

```
sizeof...(args) <= fields count
```

```
typeid(args)... == typeid(fields)...
```

```
sizeof(char) == 1
```

```
???
```

```
sizeof...(args) <= sizeof(T)
```

Ubiq

```
struct ubiq {  
    template <class Type>  
    constexpr operator Type&() const;  
};
```

```
int i = ubiq{};
```

```
double d = ubiq{};
```

```
char c = ubiq{};
```

ГОТОВО

```
static_assert(std::is_pod<T>::value, "")
```

```
T { args... }
```

```
sizeof...(args) <= fields count
```

```
typeid(args)... == typeid(fields)...
```

```
sizeof(char) == 1
```

```
struct ubiq {}
```

```
sizeof...(args) <= sizeof(T)
```

Собираем всё вместе

```
template <std::size_t I>
struct ubiq_constructor {
    template <class Type>
    constexpr operator Type&() const noexcept; // Undefined
};
```

Собираем всё вместе

```
std::make_index_sequence<5>{}
```

====>

```
std::index_sequence<0, 1, 2, 3, 4>{}
```

Собираем всё вместе

```
// #1
template <class T, std::size_t I0, std::size_t... I>
constexpr auto detect_fields_count(std::size_t& out, std::index_sequence<I0, I...>)
    -> decltype( T{ ubiq_constructor<I0>{}, ubiq_constructor<I>{}... } )
{ out = sizeof...(I) + 1;      /*...*/ }
```

```
// #2
template <class T, std::size_t... I>
constexpr void detect_fields_count(std::size_t& out, std::index_sequence<I...>) {
    detect_fields_count<T>(out, std::make_index_sequence<sizeof...(I) - 1>{});
}
```

Как получить тип поля?



Идея №2

```
T{ ubiq_constructor<I>{}... }
```


Идея №2

```
T{ ubiq_constructor<I>{}... }
```

```
ubiq_constructor<I>{}::operator Type&() const
```

Идея №2

```
T{ ubiq_constructor<I>{}... }
```

```
ubiq_constructor<I>{}::operator Type&() const
```

Type

Идея №2

```
T{ ubiq_constructor<I>{}... }
```

```
ubiq_constructor<I>{}::operator Type&() const
```

Type

```
ubiq_constructor<I>{ TypeOut& }
```

Идея №2

```
T{ ubiq_constructor<I>{}... }
```

```
ubiq_constructor<I>{}::operator Type&() const
```

Type

```
ubiq_constructor<I>{ TypeOut& }
```



Что такое POD (приблизительно)?

POD = { (public|private|protected) + (fundamental | POD)* };

Идея №2.5

fundamental (not a pointer) → int

int → output

output[I]... → Types...

Собираем идею №2.5

```
template <std::size_t I>
struct ubiq_val {
    std::size_t* ref_;

    template <class Type>
    constexpr operator Type() const noexcept {
        ref_[I] = typeid_conversions::type_to_id(identity<Type>{});
        return Type{};
    }
};
```

Собираем идею №2.5

```
#define BOOST_MAGIC_GET_REGISTER_TYPE(Type, Index) \
    constexpr std::size_t type_to_id(identity<Type>) noexcept { \
        return Index; \
    } \
    constexpr Type id_to_type( size_t_<Index > ) noexcept { \
        Type res{}; \
        return res; \
    } \
    /**/
```


Собираем идею №2.5

```
BOOST_MAGIC_GET_REGISTER_TYPE(unsigned char      , 1)
BOOST_MAGIC_GET_REGISTER_TYPE(unsigned short    , 2)
BOOST_MAGIC_GET_REGISTER_TYPE(unsigned int      , 3)
BOOST_MAGIC_GET_REGISTER_TYPE(unsigned long     , 4)
BOOST_MAGIC_GET_REGISTER_TYPE(unsigned long long, 5)
BOOST_MAGIC_GET_REGISTER_TYPE(signed char       , 6)
BOOST_MAGIC_GET_REGISTER_TYPE(short             , 7)
BOOST_MAGIC_GET_REGISTER_TYPE(int              , 8)
BOOST_MAGIC_GET_REGISTER_TYPE(long             , 9)
BOOST_MAGIC_GET_REGISTER_TYPE(long long        , 10)
```

Собираем идею №2.5

```
template <class T, std::size_t N, std::size_t... I>
constexpr auto type_to_array_of_type_ids(std::size_t* types) noexcept
    -> decltype(T{ ubiq_constructor<I>{}... })
{
    T tmp{ ubiq_val< I >{types}... };
    return tmp;
}
```

Собираем идею №2.5

```
template <class T, std::size_t... I>
constexpr auto as_tuple_impl(std::index_sequence<I...>) noexcept {
    constexpr auto a = array_of_type_ids<T>();           // #0

    return std::tuple<                                   // #3
        decltype(typeid_conversions::id_to_type(        // #2
            size_t_<a[I]>{}                               // #1
        ))...
    >{};
}
```

Что делать с указателями на
указатели на константные
указатели на <...> на
фундаментальный тип?



Поддерживаем сложные указатели

```
constexpr std::size_t type_to_id(identity<Type>)
```

Поддерживаем сложные указатели

```
constexpr std::size_t type_to_id(identity<Type>)  
    sizeof(std::size_t) * 8 == 64/32 bits
```

Поддерживаем сложные указатели

```
constexpr std::size_t type_to_id(identity<Type>)
```

```
sizeof(std::size_t) * 8 == 64/32 bits
```

```
fundamental types < 32
```

Поддерживаем сложные указатели

```
constexpr std::size_t type_to_id(identity<Type>)
```

```
sizeof(std::size_t) * 8 == 64/32 bits
```

fundamental types < 32

fundamental types require 5 bits

Enums?



Enums

```
template <class Type>
constexpr std::size_t type_to_id(identity<Type>,
    typename std::enable_if<std::is_enum<Type>::value>::type*) noexcept
{
    return type_to_id(identity<
        typename std::underlying_type<Type>::type
    >{});
}
```

Вложенные структуры и
классы?



Вложенные структуры

```
template <class Type>
constexpr auto type_to_id(identity<Type>, typename std::enable_if<
    !std::is_enum<Type>::value && !std::is_empty<Type>::value>::type*) noexcept
{
    return array_of_type_ids<Type>(); // Returns array!
}
```

Вложенные структуры

```
// ... in struct ubiq_val
template <class Type>
constexpr operator Type() const noexcept {
    constexpr auto typeids = typeid_conversions::type_to_id(identity<Type>{});
    assign(typeids);
    return Type{};
}
```

Вложенные структуры

```
// ... in struct ubiq_val
```

```
constexpr void assign(std::size_t val) const noexcept {  
    ref_[I] = val;  
}
```

```
template <class T>
```

```
constexpr void assign(const T& typeids) const noexcept {
```

```
    for (std::size_t i = 0; i < T::size(); ++i)
```

```
        ref_[I + i] = typeids.data[i]; // ref_[I + I] must not overlap with next field
```

```
}
```

Место под хранение ТИПОВ

```
std::size_t output[sizeof(T)];
```

```
I == sizeof(PrevFields) + ...
```

Место под хранение типов

```
struct foo1 { short s; unsigned char i; };           // { 7, 0, 1, 0};
```


Место под хранение ТИПОВ

```
struct foo1 { short s; unsigned char i; }; // { 7, 0, 1, 0};
```

```
struct foo2 { unsigned char i; foo1 f;}; // {1, 7, 0, 1, 0, 0};
```

Место под хранение ТИПОВ

```
struct foo1 { short s; unsigned char i; };           // { 7, 0, 1, 0};  
  
struct foo2 { unsigned char i; foo1 f;};           // {1, 7, 0, 1, 0, 0};  
  
struct foo3 { foo1 f0; foo1 f; };                 // {7, 0, 1, 0, 7, 0, 1, 0};
```

Место под хранение ТИПОВ

```
struct foo1 { short s; unsigned char i; };           // { 7, 0, 1, 0};  
  
struct foo2 { unsigned char i; foo1 f;};           // {1, 7, 0, 1, 0, 0};  
  
struct foo3 { foo1 f0; foo1 f; };                 // {7, 0, 1, 0, 7, 0, 1, 0};  
  
struct foo4 { foo2 f0; foo1 f; };                 // {1, 7, 0, 1, 0, 0, 7, 0, 1, 0};
```

Что это нам даёт?



Что это даёт?

- Сравнения : `<`, `<=`, `>`, `>=`, `!=`, `==`
- Гетерогенные сравнения: `flat_less<>`, `flat_equal<>`
- Операторы ввода/вывода: `operator <<`, `operator >>`
- Хеширование: `flat_hash<>`
- Пользовательские сериализаторы
- Базовая рефлексия
- Новые `type_traits`: `is_continuous_layout<T>`, `is_padded<T>`, `is_uniquely_represented<T>`
- Новые возможности для контейнеров: `punch_hole<T, Index>`
- Более обобщённые алгоритмы: `vector_mult`, `parse to struct`

Примеры

```
namespace foo {  
    struct comparable_struct {  
        int i; short s; char data[50]; bool bl; int a,b,c,d,e,f;  
    };  
    using namespace pod_ops;  
} // namespace foo
```

```
std::set<foo::comparable_struct> s;
```

Примеры

```
std::set<foo::comparable_struct> s = { /* ... */ };
```

```
std::ofstream ofs("dump.txt");
```

```
for (auto& a: s)
```

```
    ofs << a << '\n';
```

Примеры

```
std::set<foo::comparable_struct> s;  
std::ifstream ifs("dump.txt");
```

```
foo::comparable_struct cs;
```

```
while (ifs >> cs) {  
    char ignore = {};  
    ifs >> ignore;  
    s.insert(cs);  
}
```


| Спасибо за внимание! Вопросы?

https://github.com/apolukhin/magic_get

C++17



C++17

```
template <class T>
constexpr auto as_tuple(T& val) noexcept {
    typedef size_t_<fields_count<T>()> fields_count_tag;
    return detail::as_tuple_impl(val, fields_count_tag{});
}
```

C++17

```
template <class T>
constexpr auto as_tuple(T& val) noexcept {
    typedef size_t_<fields_count<T>()> fields_count_tag;
    return detail::as_tuple_impl(val, fields_count_tag{});
}
```

Structured bindings

```
template <class T>
constexpr auto as_tuple_impl(T&& val, size_t_<1>) noexcept {
    auto& [a] = std::forward<T>(val);
    return detail::make_tuple_of_references(a);
}
```

```
template <class T>
constexpr auto as_tuple_impl(T&& val, size_t_<2>) noexcept {
    auto& [a,b] = std::forward<T>(val);
    return detail::make_tuple_of_references(a,b);
}
```

Structured bindings

```
template <class T>
constexpr auto as_tuple_impl(T&& val, size_t_<1>) noexcept {
    auto& [a] = std::forward<T>(val);
    return detail::make_tuple_of_references(a);
}
```

```
template <class T>
constexpr auto as_tuple_impl(T&& val, size_t_<2>) noexcept {
    auto& [a,b] = std::forward<T>(val);
    return detail::make_tuple_of_references(a,b);
}
```

| Спасибо за внимание! Вопросы?

https://github.com/apolukhin/magic_get